



# INTERIORS – D20

## Acrylic Distemper

Birla Opus Prime D20 Interior Acrylic Distemper offers a rich and beautiful look to the walls. It is an acrylic-based distemper that boasts high washability with a diverse palette of colors.

### PRODUCT FEATURES



#### RICH LOOK & FINISH

Uniform distribution contributing to a professional and polished look.



#### WIDE RANGE OF COLOURS

Wide spectrum of shades and colours to suit every project need.



#### HIGH WASHABILITY

Advanced washability formula for pristine surfaces and effortless maintenance.



#### EXCELLENT WHITENESS

Infusing your walls with an excellent white quality paint enhancing their overall appearance.



#### WARRANTY\*

Long lasting assurance on film integrity and colour retention.

### PRODUCT DETAILS


#### AVAILABLE PACKS



#### COVERAGE

Only on the correctly prepared surface using brush/roller:

**70-90 sq.ft/kg/2 coats\*\***



\*\*Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity. One should ensure coverage is not higher than the one prescribed above for optimal performance.

#### COLOUR AVAILABLE

**1000+**




#### FINISH



**MATT**

### DIRECTION FOR USE

#### PRE PAINTING STEPS / SURFACE PREPARATION



**1.** Strip all old / previously applied unadhering paint / papdi, flaking particles, plaster, dirt, dust, grease, wax, fungus or any other microbial growth by putty knife and / or sanding with emery paper No. 180 and wipe off.



**3.** In case of water leakage / seepage, special treatment of water proofing is required.



**2.** In heavy fungus or microbial growth affected area, special treatment of biowash is required.



**4.** Ensure surface is clean & completely dry before starting the painting procedures.

## PAINTING STEPS



**1.** Apply one coat of Birla Opus Prime Interior Wall Primer (Water thinnable/Solvent thinnable). Allow it to dry for 4-6 hours in case of water thinnable primer & 6-8 hours for solvent thinnable primer



**3.** Apply one coat of Birla Opus Prime Interior Wall Primer (Water thinnable/Solvent thinnable). Allow it to dry for 4-6 hours in case of water thinnable primer & 6-8 hours for solvent thinnable primer.



**2.** Apply 1-2 coats of Birla Opus One Acrylic Putty to fill dents, minor cracks and to smoothen & level the surface. Allow it to dry 4-6 hours. Sand with emery paper no. 180/320 & wipe off loose powder.



**4.** Dilute 1kg Birla Opus Prime D20 Acrylic Distemper with 600-650ml of clean water and apply 2-3 coats by using brush & roller or by roller at an interval between 4-6 hours between each coat.

## POST PAINTING CARE

**1**

Paint film generally require 2 weeks to develop adequate strength.

**2**

A clean and well-maintained living space will aid in long lasting finish.

## TECHNICAL DATA

Drying time	Surface dry time 30-45 min*
Recoating time	4-6 hours*
Thinning	60-65% by clean water
Flash point	Not applicable. Non-flammable water based product
Usage time (to be used post dilution)	Within 24 hours*
Shelf life	36 Months

\*Varies on climatic conditions.

## SAFETY FEATURES

- Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hours of application.
- Do not add extra water.
- Tint using Birla Opus machine colourants only.
- Stir well and strain before use.
- Tinted paints need thorough shaking immediately after Birla Opus colorant addition as well as before use.
- Store the container in ventilated locations and away from sources of ignition and fire.
- Kindly refer to the MSDS, which gives detailed information on safety measures while handling the paint, which is available on request.
- Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- Keep out of reach of children and away from eatables.
- May be harmful if swallowed. In case of ingestion, seek immediate medical attention.
- Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- Left-over paint/drums should not be disposed in soil or drains.
- Consumer should consult a local recycling agency for proper disposal of paint/drums.